

VALVE REGULATED LEAD ACID RECHARGEABLE BATTERIES

Standard Series

MODEL	NOMINAL VOLTAGE V	NOMINAL CAPACITY @20 HR RATE AH	DIMENSIONS (MM) (TOLERANCE ± 2MM)				TERMINAL TYPE	CARTON QUANTITY
			LENGTH	WIDTH	HEIGHT	TH		
PS-610	6	1.0	50	42	51	57	F1	20
PS-612	6	1.3	97	24	51.5	57.5	F1	20
PS-630	6	3.4	134	34	60	66	F1	20
PS-640	6	4.5	70	47	100	106	F1	20
PS-670	6	7.0	151	34	94	100	F1	10
PS-682	6	8.0	98	56	118	120	F1	10
PS-6100	6	10.0	151	51	94	100	F1	10
PS-1212	12	1.2	97	43	52	58	F1	20
PS-1221	12	2.1	178	35	60	66	F1	20
PS-1230	12	3.4	134	67	60.5	66.5	F1	10
PS-1242	12	4.5	90	70	101	107	F1	10
PS-1270	12	7.0	151	65	94	100	F1	5
PS-12120	12	12.0	151	98	95	101	F1	4
PS-12170	12	17.0	181.5	77	167.5	167.5	T12	2
PS-12260	12	26.0	166.5	176	112	125	T12	2
PS-12350	12	35.0	195	130	164	177	T5	1
PS-12380	12	38.0	197	165	170	170	T6	1
PS-12450	12	45.0	197	165	170	170	T6	1
PS-12550	12	55.0	229	138	205	226	T6	1
PS-12650	12	65.0	348	167	178	178	T6	1
PS-12750	12	75.0	259	168	206	212	T6	1
PS-121000	12	100.0	305	168	206	212	T6	1

Terminal Types:

F1 = 4.75mm width

T5 = Nut & bolt

WL = Wire lead with JST plug

T6 = Threaded insert 6mm stud

T12 = Threaded insert 5mm stud

Indicates VdS and NCP approved model

All models supplied in Power-Sonic standard blue/grey plastic cases.

**THIS IS A SELECTION OF OUR MOST POPULAR MODELS ONLY.
IF THE BATTERY YOU REQUIRE IS NOT LISTED HERE, PLEASE CONTACT US.**

FOR DETAILED INFORMATION ON INDIVIDUAL MODELS PLEASE
CONTACT US OR REFER TO OUR WEBSITE - www.power-sonic.co.uk

